


This Local Development Plan (LDP) has been approved by the City of Kwinana under the provisions of Local Planning Scheme No.2 and Schedule 2 (Deemed Provisions) of the Planning and Development (Local Planning Schemes) Regulations 2015. This is an amendment to an existing approved LDP and is valid for the period specified in this approval.

DA10752.2	07/11/2024
Delegated Authority	Amendment Date
City of Kwinana	30/04/2034
	Expiry Date



LEGEND

----- Local Development Plan Boundary	R25 Coding	R30 Coding
R40 Coding	Designated Garage Location	BAL Affected Lots
Primary Dwelling Orientation	Secondary Dwelling Orientation	Asset Protection Zone
Footpaths	Retaining Wall	No Vehicle Access
Approximate street tree location. Refer to approved Landscaping Plan available from the City for detail. Street trees are not to be removed or relocated by landowners.		
Retained Trees		
Upper Floor - Package A Ground Floor - Standard Construction		
Upper Floor - Package A Ground Floor - Package A		
Upper Floor - Package B Ground Floor - Package A		
Upper Floor - Package B Ground Floor - Package B		

This Local Development Plan (LDP) has been approved by the City of Kwinana under the provisions of Local Planning Scheme No.2 and Schedule 2 (Deemed Provisions) of the Planning and Development (Local Planning Schemes) Regulations 2015. This is an amendment to an existing approved LDP and is valid for the period specified in this approval.

DA10752.2	07/11/2024
Delegated Authority	Amendment Date
City of Kwinana	30/04/2034
	Expiry Date

LOCAL DEVELOPMENT PLAN

Stage 49 The Village at Wellard Page 2 of 7

A PEET Limited and Department of Housing Joint Venture Project

Scale: 1:1500 @ A3

PLAN: PACWE-4-042
DATE: 13/02/2024
PROJECTION: PCG 94
DATUM: AHD

REVISION:
DRAWN: JP
PLANNER: KG
CHECK: CH

cdp

Town Planning & Urban Design

Unit 2, 464 Murray Street
Perth WA 6000
(08) 6333 1888
info@cdpau.com.au
www.cdpau.com.au

Copyright CDP. No part of this plan may be reproduced in any form without prior consent from CDP. All care has been taken in preparation of this plan but no responsibility is taken for any errors or omissions and is subject to change. Areas and dimensions shown on plan are subject to final survey. Carriageways depicted on plan are diagrammatic only.

LOCAL DEVELOPMENT PLAN PROVISIONS - THE VILLAGE AT WELLARD STAGE 38, 40, 49

The provisions addressed below and on the reverse plan relate to Stage 38, 40 & 49 within The Village at Wellard Estate, Wellard. The requirements of the Residential Design Codes (R-Codes) apply, unless otherwise provided for below.

The following standards represent variations to the R-Codes and constitute ‘deemed-to-comply’ requirements, pursuant to the R-Codes.

1. R-CODE VARIATIONS		
a.	Minimum Open Space*:	
i.	R25:	40%
ii.	R30	35%
iii.	R40:	30%
NOTES:		
*NB: <ul style="list-style-type: none">Minimum open space may be reduced to:<ul style="list-style-type: none">40% for R25 lots, subject to the provision of a 30m² Outdoor Living Area.35% for R30 lots, subject to the provisions of a 20m² Outdoor Living Area.30% for R40 lots, subject to the provision of a 20m² Outdoor Living Area.In all instances, a minimum of 4m is required, with two-thirds of this area uncovered and located behind the street setback area.		
2. SETBACK PROVISIONS		
	Minimum	Maximum
a.	Dwelling:	
i.	Primary Street:	
	R25	3.0m 5.0m
	Lots 1783 – 1786 & 1801	3.0m 6.0m
	R30 & R40	2.0m 4.0m
b.	Garage:	
i.	Primary Street	4.5m -
ii.	Secondary Street (No Footpath)	Nil -
iii.	Secondary Street (With Footpath)	1.5m -
c.	Boundary Walls (Parapets):	For all R30 & R40 lots, and lots with a frontage of 11 metres or less, lot boundary walls are permitted to both side boundaries for a maximum length prescribed by the front and rear setback requirements (with the exception of side street boundaries).

3. BUILDING FORM, ORIENTATION & DWELLING FAÇADE

- a. The design of dwellings shall include an articulated front elevation in the direction of the ‘*Primary Dwelling Orientation*’ arrow shown on the Local Development Plan. The front elevation shall consist of at least one major opening to a habitable room overlooking the ‘*Primary Dwelling Orientation*’.
- b. The design of dwellings on applicable lots shall include a side elevation, which has at least one major opening facing the direction of the ‘*Secondary Dwelling Orientation*’ arrow shown on the Local Development Plan.
- The part of the dwelling which includes the required major opening shall be well articulated and its view not obstructed by visually impermeable fencing.
- c. All dwellings to provide an appropriate, high quality design interface with the surrounding streetscape, through the use of at least three of the following architectural design features:
- i. Articulation in dwelling façade (i.e. varied wall setbacks);
- ii. A minimum of two building materials, colours and/or finishes (e.g. render, brick cladding);
- iii. Major habitable room openings incorporate large windows to provide surveillance;
- iv. Roof forms that incorporate gables;
- v. A balcony, portico, or verandah; or
- vi. A built-in planter box.
- d. Where possible, dwellings are to be designed to take advantage of northern solar orientation.
- e. A 4m² store room shall be provided for all single dwellings on lots with a frontage of 7.5m or less, in accordance with the requirements of Clause 5.4.4 C4.5 of **State Planning Policy 7.3 Residential Design Codes Volume 1**.

4. VEHICULAR ACCESS & GARAGES/CARPORTS

- a. All garages are to have doors to enclose them.
- b. Designated garage locations apply to lots identified on the Local Development Plan; this is referencing the side of the lot to which the garage location is recommended. Designated garage locations do not prescribe boundary walls.
- c. Garages are not to be forward of the dwelling alignment. Garages may be aligned with the dwelling, provided they do not exceed the dwelling setback line.
- d. Where lots have a frontage of ≤12 metres, garages may exceed 50% of the primary lot frontage to a maximum of 60% of the primary lot frontage.
- e. Where garages exceed 50% of the primary lot frontage, they shall comply with the following:
- i. A clear indication of the dwelling entrance.
- ii. The dwelling entrance shall be the dominant feature of the façade, and shall include a portico or verandah, forward of the dwelling alignment with a minimum depth of 1.5 metres.
- iii. Garages are to be setback at least 0.5 metres behind the dwelling alignment.
- f. For any single storey dwelling with a frontage ≤10 metres in width and where vehicle access is gained solely from the primary street, only a single width garage/carport (including tandem) is permitted.
- g. Double garages are permitted on lots <10 metres wide where dwellings are two-storeys and where major openings to habitable rooms are provided on the primary street frontage.
- h. For all lots where a footpath adjoins the boundary, the garage must be setback a minimum of 4.5 metres where it adjoins the primary street setback.

5. UNIFORM ESTATE BOUNDARY FENCING

- a. Any estate provided fencing/retaining on private lots shall not be modified without written approval from the City and shall be maintained as visually permeable by landowners where applicable.

6. FENCING

- a. Front fences within the primary street setback shall be visually permeable above 0.9 metres, to a maximum height of 1.2 metres above natural ground level.
- b. For secondary street boundaries, fencing shall be visually permeable above 1.2 metres behind the primary street setback, for a minimum length of 3 metres behind the truncation, with a habitable room addressing the street.
- c. For corner lots, with a boundary of over 25m which have a garage located to the primary street, fencing along the secondary street boundary shall be visually permeable above 1.2 metres behind the primary street setback, for a minimum length of 6 metres behind the truncation, with a habitable room addressing the secondary street.

7. BUSHFIRE MANAGEMENT

- a. The land subject of this LDP is within a bushfire prone area, as designated by the Department of Fire and Emergency Services. Those lots identified on this LDP as being subject to a Bushfire Management Plan require a Bushfire Attack Level (BAL) Assessment prior to construction, in accordance with AS 3959.

8. STREET TREES

- a. In accordance with the City’s Streetscape Policy, a minimum of one street tree per lot is required (or as agreed with the City). Street trees will be provided by the developer within the road verge and maintained for a minimum of two years until established (or as agreed with the City). Street trees are to be generally located as shown on the Local Development Plan, subject to detailed landscape design and crossover locations. Refer to approved Landscape Plans (available from the City) for detail. Street trees are not to be relocated or removed by landowners.

9. ACOUSTICS

- a. ‘Package A’ and ‘Package B’ – Deemed to satisfy Construction Standards are required for upper and lower floor dwellings as identified on the LDP in accordance with the recommendations of the *Transport Noise Assessment Report – Lloyd George Acoustics, April 2023 (Reference: 14012644-03)*.
- b. Building permit applications to the City of Kwinana must demonstrate compliance with the relevant ‘Deemed to Satisfy Construction Standards’, including the provision of mechanical ventilation.

10. NOTIFICATION TO PROSPECTIVE PURCHASERS

- a. The developer is required to give prospective purchasers a complete copy of all the requirements of this Local Development Plan prior to Offer and Acceptance being made.

LOCAL DEVELOPMENT PLAN

Stages 38, 40 & 49 The Village at Wellard Page 3 of 7

A PEET Limited and Department of Housing Joint Venture Project

PLAN: PACWE-4-042
DATE: 29/07/2024
PROJECTION: PCG 94
DATUM: AHD
REVISION: B
DRAWN: JP
PLANNER: CH
CHECK: CH




Unit 2, 464 Murray Street
Perth WA 6000
(08) 6333 1888
info@cdpaus.com.au
www.cdpaus.com.au
Copyright CDP. No part of this plan may be reproduced in any form without prior consent from CDP. All care has been taken in preparation of this plan but no responsibility is taken for any errors or omissions and is subject to change. Areas and dimensions shown on plan are subject to final survey. Carriageways depicted on plan are diagrammatic only.

The packages and information provided on the following pages are taken from *Road and Rail Noise Guidelines* (September 2019).

Where outdoor and indoor noise levels received by a noise-sensitive land-use and/or development exceed the policy's noise target, implementation of quiet house requirements is an acceptable solution.

With regards to the packages, the following definitions are provided:

- **Facing** the transport corridor (red): Any part of a building façade is 'facing' the transport corridor if any straight line drawn perpendicular (at a 90 degree angle) to its nearest road lane or railway line intersects that part of the façade without obstruction (ignoring any fence).
- **Side-on** to transport corridor (blue): Any part of a building façade that is not 'facing' is 'side-on' to the transport corridor if any straight line, at any angle, can be drawn from it to intersect the nearest road lane or railway line without obstruction (ignoring any fence).
- **Opposite** to transport corridor (green): Neither 'side on' nor 'facing', as defined above.



Quiet House Package A

56-58 dB $L_{Aeq}(\text{Day})$ & 51-53 dB $L_{Aeq}(\text{Night})$

Element	Orientation	Room	
		Bedroom	Indoor Living and Work Areas
External Windows	Facing	<ul style="list-style-type: none"> Up to 40% floor area ($R_w + C_{tr} \geq 28$): <ul style="list-style-type: none"> Sliding or double hung with minimum 10mm single or 6mm-12mm-10mm double insulated glazing; Sealed awning or casement windows with minimum 6mm glass. Up to 60% floor area ($R_w + C_{tr} \geq 31$): <ul style="list-style-type: none"> Sealed awning or casement windows with minimum 6mm glass. 	<ul style="list-style-type: none"> Up to 40% floor area ($R_w + C_{tr} \geq 25$): <ul style="list-style-type: none"> Sliding or double hung with minimum 6mm single or 6mm-12mm-6mm double insulated glazing; Up to 60% floor area ($R_w + C_{tr} \geq 28$); Up to 80% floor area ($R_w + C_{tr} \geq 31$).
	Side On	As above, except $R_w + C_{tr}$ values may be 3 dB less or max % area increased by 20%.	
	Opposite	No specific requirements	
External Doors	Facing	<ul style="list-style-type: none"> Fully glazed hinged door with certified $R_w + C_{tr} \geq 28$ rated door and frame including seals and 6mm glass. 	<ul style="list-style-type: none"> Doors to achieve $R_w + C_{tr} \geq 25$: <ul style="list-style-type: none"> 35mm Solid timber core hinged door and frame system certified to $R_w 28$ including seals; Glazed sliding door with 10mm glass and weather seals.
	Side On	As above, except $R_w + C_{tr}$ values may be 3 dB less.	
	Opposite	No specific requirements	
External Walls	All	<ul style="list-style-type: none"> $R_w + C_{tr} \geq 45$: <ul style="list-style-type: none"> Two leaves of 90mm thick clay brick masonry with minimum 20mm cavity; or Single leaf of 150mm brick masonry with 13mm cement render on each face; or One row of 92mm studs at 600mm centres with: <ul style="list-style-type: none"> Resilient steel channels fixed to the outside of the studs; and 9.5mm hardboard or fibre cement sheeting or 11mm fibre cement weatherboards fixed to the outside; 75mm thick mineral wool insulation with a density of at least 11kg/m³; and 2 x 16mm fire-rated plasterboard to inside. 	
Roofs and Ceilings	All	<ul style="list-style-type: none"> $R_w + C_{tr} \geq 35$; Concrete or terracotta tile or metal sheet roof with sarking and at least 10mm plasterboard. 	
Outdoor Living Areas		At least one outdoor living area located on the opposite side of the building from the transport corridor and/or at least one ground level outdoor living area screened using a solid continuous fence or other structure of minimum 2 metres height above ground level.	

Quiet House Package B

59-62 dB $L_{Aeq}(\text{Day})$ & 54-57 dB $L_{Aeq}(\text{Night})$

Element	Orientation	Room	
		Bedroom	Indoor Living and Work Areas
External Windows	Facing	<ul style="list-style-type: none"> Up to 40% floor area ($R_w + C_{tr} \geq 31$): <ul style="list-style-type: none"> Fixed sash, awning or casement with minimum 6mm glass or 6mm-12mm-6mm double insulated glazing. Up to 60% floor area ($R_w + C_{tr} \geq 34$): <ul style="list-style-type: none"> Fixed sash, awning or casement with minimum 10mm glass or 6mm-12mm-10mm double insulated glazing. 	<ul style="list-style-type: none"> Up to 40% floor area ($R_w + C_{tr} \geq 28$): <ul style="list-style-type: none"> Sliding or double hung with 6mm-12mm-10mm double insulated glazing; Sealed awning or casement windows with minimum 6mm glass. Up to 60% floor area ($R_w + C_{tr} \geq 31$); Up to 80% floor area ($R_w + C_{tr} \geq 34$).
	Side On	As above, except $R_w + C_{tr}$ values may be 3 dB less or max % area increased by 20%.	
	Opposite	As above, except $R_w + C_{tr}$ values may be 6 dB less or max % area increased by 20%.	
External Doors	Facing	<ul style="list-style-type: none"> Fully glazed hinged door with certified $R_w + C_{tr} \geq 31$ rated door and frame including seals and 10mm glass. 	<ul style="list-style-type: none"> Doors to achieve $R_w + C_{tr} \geq 28$: <ul style="list-style-type: none"> 40mm Solid timber core hinged door and frame system certified to R_w 32 including seals; Fully glazed hinged door with certified $R_w + C_{tr} \geq 28$ rated door and frame including seals and 6mm glass.
	Side On	As above, except $R_w + C_{tr}$ values may be 3 dB less or max % area increased by 20%.	
	Opposite	As above, except $R_w + C_{tr}$ values may be 6 dB less or max % area increased by 20%.	
External Walls	All	<ul style="list-style-type: none"> $R_w + C_{tr} \geq 50$: <ul style="list-style-type: none"> Two leaves of 90mm thick clay brick masonry with minimum 50mm cavity between leaves and 25mm glasswool or polyester (24kg/m³). Resilient ties used where required to connect leaves. Two leaves of 110mm clay brick masonry with minimum 50mm cavity between leaves and 25mm glasswool or polyester insulation (24kg/m³). Single leaf of 220mm brick masonry with 13mm cement render on each face. 150mm thick unlined concrete panel or 200mm thick concrete panel with one layer of 13mm plasterboard or 13mm cement render on each face. Single leaf of 90mm clay brick masonry with: <ul style="list-style-type: none"> A row of 70mm x 35mm timber studs or 64mm steel studs at 600mm centres; A cavity of 25mm between leaves; 50mm glasswool or polyester insulation (11kg/m³) between studs; and One layer of 10mm plasterboard fixed to the inside face. 	
Roofs and Ceilings	All	<ul style="list-style-type: none"> $R_w + C_{tr} \geq 35$: <ul style="list-style-type: none"> Concrete or terracotta tile or metal sheet roof with sarking and at least 10mm plasterboard ceiling with R3.0+ fibrous insulation. 	
Outdoor Living Areas		At least one outdoor living area located on the opposite side of the building from the transport corridor and/or at least one ground level outdoor living area screened using a solid continuous fence or other structure of minimum 2.4 metres height above ground level.	

Quiet House Package C

63-66 dB $L_{Aeq}(\text{Day})$ & 58-61 dB $L_{Aeq}(\text{Night})$

Element	Orientation	Room	
		Bedroom	Indoor Living and Work Areas
External Windows	Facing	<ul style="list-style-type: none"> Up to 20% floor area ($R_w + C_{tr} \geq 31$): <ul style="list-style-type: none"> Fixed sash, awning or casement with minimum 6mm glass or 6mm-12mm-6mm double insulated glazing. Up to 40% floor area ($R_w + C_{tr} \geq 34$): <ul style="list-style-type: none"> Fixed sash, awning or casement with minimum 10mm glass or 6mm-12mm-10mm double insulated glazing. 	<ul style="list-style-type: none"> Up to 40% floor area ($R_w + C_{tr} \geq 31$): <ul style="list-style-type: none"> Fixed sash, awning or casement with minimum 6mm glass or 6mm-12mm-6mm double insulated glazing. Up to 60% floor area ($R_w + C_{tr} \geq 34$): <ul style="list-style-type: none"> Fixed sash, awning or casement with minimum 10mm glass or 6mm-12mm-10mm double insulated glazing.
	Side On	As above, except $R_w + C_{tr}$ values may be 3 dB less or max % area increased by 20%.	
	Opposite	As above, except $R_w + C_{tr}$ values may be 6 dB less or max % area increased by 20%.	
External Doors	Facing	<ul style="list-style-type: none"> Not recommended. 	<ul style="list-style-type: none"> Doors to achieve $R_w + C_{tr} \geq 30$: <ul style="list-style-type: none"> Fully glazed hinged door with certified $R_w + C_{tr} \geq 31$ rated door and frame including seals and 10mm glass; 40mm Solid timber core side hinged door, frame and seal system certified to $R_w 32$ including seals. Any glass inserts to be minimum 6mm.
	Side On	As above, except $R_w + C_{tr}$ values may be 3 dB less or max % area increased by 20%.	
	Opposite	As above, except $R_w + C_{tr}$ values may be 6 dB less or max % area increased by 20%.	
External Walls	All	<ul style="list-style-type: none"> $R_w + C_{tr} \geq 50$: <ul style="list-style-type: none"> Two leaves of 90mm thick clay brick masonry with minimum 50mm cavity between leaves and 25mm glasswool or polyester insulation (24kg/m^3). Resilient ties used where required to connect leaves. Two leaves of 110mm clay brick masonry with minimum 50mm cavity between leaves and 25mm glasswool or polyester insulation (24kg/m^3). Single leaf of 220mm brick masonry with 13mm cement render on each face. 150mm thick unlined concrete panel or 200mm thick concrete panel with one layer of 13mm plasterboard or 13mm cement render on each face. Single leaf of 90mm clay brick masonry with: <ul style="list-style-type: none"> A row of 70mm x 35mm timber studs or 64mm steel studs at 600mm centres; A cavity of 25mm between leaves; 50mm glasswool or polyester insulation (11kg/m^3) between studs; and One layer of 10mm plasterboard fixed to the inside face. 	
Roofs and Ceilings	All	<ul style="list-style-type: none"> $R_w + C_{tr} \geq 40$: <ul style="list-style-type: none"> Concrete or terracotta tile roof with sarking, or metal sheet roof with foil backed R2.0+ fibrous insulation between steel sheeting and roof battens; R3.0+ insulation batts above ceiling; 2 x 10mm plasterboard ceiling or 1 x 13mm sound-rated plasterboard affixed using steel furring channel to ceiling rafters. 	
Outdoor Living Areas		At least one outdoor living area located on the opposite side of the building from the transport corridor and/or at least one ground level outdoor living area screened using a solid continuous fence or other structure of minimum 2.4 metres height above ground level.	